

ARDEX WPM 501 - PART A

Chemwatch Material Safety Data Sheet
Issue Date: 11-Mar-2006

Revision No: 2

Hazard Alert Code:
HIGH
Chemwatch 4560-93
CD 2006/2

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ARDEX WPM 501 - PART A

SYNONYMS

"Shelter HydrEpoxy 501 Adhesive -Part A"

PRODUCT USE

Part A of a two component water-based epoxy adhesive.

SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road


Seven Hills

NSW, 2147

AUS

Telephone: 1800 224 070

Fax: +61 2 9838 7817

HAZARD RATINGS**Section 2 - HAZARDS IDENTIFICATION****STATEMENT OF HAZARDOUS NATURE**

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

May cause SENSITISATION by skin contact.

Inhalation may produce health damage*.

Cumulative effects may result following exposure*.

May produce discomfort of the eyes, respiratory tract and skin*.

Limited evidence of a carcinogenic effect*.

Possible respiratory sensitiser*.

May be harmful to the foetus/ embryo*.

* (limited evidence).

SAFETY

Keep container in a well ventilated place.

Avoid exposure - obtain special instructions before use.

Keep container tightly closed.

Take off immediately all contaminated clothing.

In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyamide resin	Not avail.	30-60
triethylenetetramine	112-24-3	<2
ingredients determined not to be hazardous		30-70

Section 4 - FIRST AID MEASURES**SWALLOWED**

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

ARDEX WPM 501 - PART A

Chemwatch Material Safety Data Sheet
Issue Date: 11-Mar-2006

Revision No: 2

Hazard Alert Code:
HIGH

Chemwatch 4560-93
CD 2006/2

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES**EXTINGUISHING MEDIA**

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include.

carbon dioxide (CO₂).

nitrogen oxides (NO_x).

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

None

Personal Protective Equipment

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES**EMERGENCY PROCEDURES****MINOR SPILLS**

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.

ARDEX WPM 501 - PART A

Chemwatch Material Safety Data Sheet

Revision No: 2

Hazard Alert Code:

HIGH

Chemwatch 4560-93

Issue Date: 11-Mar-2006

CD 2006/2

- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

X: Must not be stored together

O: May be stored together with specific preventions

+: May be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.**Section 7 - HANDLING AND STORAGE****PROCEDURE FOR HANDLING**

DO NOT allow clothing wet with material to stay in contact with skin.

DO NOT use aluminium, galvanised or tin-plated containers.

DO NOT USE brass or copper containers / stirrers.

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE CONTROLS**

The following materials had no OELs on our record under the following CAS or Chemwatch (CW) numbers

Ardex WPM 501 - Part A: No data available for CW:4560-93

polyamide resin: No data available for CW:85010

triethylenetetramine: No data available for CAS:112-24-3

EMERGENCY EXPOSURE LIMITS

Not available. Refer to individual constituents.

EXPOSURE STANDARDS FOR MIXTURE

"Worst Case" computer-aided prediction of vapour components/concentrations:

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m³): 6 mg/m³

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the

ARDEX WPM 501 - PART AHazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 2

Chemwatch 4560-93

Issue Date: 11-Mar-2006

CD 2006/2

individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc: (%)

Component	Breathing zone (ppm)	Breathing Zone (mg/m ³)	Mixture Conc (%)
triethylenetetramine	1.00	6.0000	2.0

Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

At the "Composite Exposure Standard for Mixture" (TWA) (mg/m³): 2 mg/m³**REPRODUCTIVE HEALTH GUIDELINES**

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	TLV Adeq
triethylenetetramine	2.9 mg/m ³	10	D	NA	-

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive
American Industrial Hygiene Association Journal 57: 641-649 (1996).**INGREDIENT DATA**

POLYAMIDE RESIN:

No exposure limits set by NOHSC or ACGIH.

TRIETHYLENETETRAMINE:

No exposure limits set by NOHSC or ACGIH. CEL TWA: 1 ppm, 6 mg/m³; STEL: 2 ppm, 12 mg/m³ [compare OEL TWA (Sweden): 1 ppm, 6 mg/m³; STEL: 2 ppm, 12 mg/m³ Sensitiser]**PERSONAL PROTECTION****EYE**

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]

HANDS/FEET

- When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butadiene rubber), boots and aprons.
- DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).
- DO NOT use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Respiratory protection is required when ANY "Worst Case" vapour-phase concentration is exceeded (see Computer Prediction in "Exposure Standards").

Protection Factor (Min)	Half-Face Respirator	Full-Face Respirator
10 x ES	AK-AUS	-

ARDEX WPM 501 - PART AHazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 2

Chemwatch 4560-93

Issue Date: 11-Mar-2006

CD 2006/2

	AK-PAPR-AUS	-
50 x ES	-	AK-AUS
	-	AK-PAPR-AUS
100 x ES	-	AK-2
	-	AK-PAPR-2

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE**

Black paste with a mild amine odour; emulsifies in water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: Not applicable

Melting Range (°C): Not available

Solubility in water (g/L): Partly miscible

pH (1% solution): Not available

Volatile Component (%vol): 47-53

Relative Vapour Density (air=1): Not available

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not applicable

State: Liquid

Boiling Range (°C): 100

Specific Gravity (water=1): 0.96-1.00

pH (as supplied): 9.5-10.5

Vapour Pressure (kPa): Not available

Evaporation Rate: Not available

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): Not available

Viscosity: Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION**CONDITIONS CONTRIBUTING TO INSTABILITY**

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

ARDEX WPM 501 - PART AHazard Alert Code:
HIGH

Chemwatch Material Safety Data Sheet

Revision No: 2

Chemwatch 4560-93

Issue Date: 11-Mar-2006

CD 2006/2

POTENTIAL HEALTH EFFECTS**ACUTE HEALTH EFFECTS****SWALLOWED**

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

This material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.

Vapours of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in "halos" around lights. This effect is temporary, lasting only for a few hours. However this condition can reduce the efficiency of undertaking skilled tasks, such as driving a car. Direct eye contact with liquid volatile amines may produce eye damage, permanent for the lighter species.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Volatile amine vapours produce irritation and inflammation of the skin. Direct contact can cause burns. They may be absorbed through the skin and cause similar effects to swallowing, leading to death. The skin may exhibit whiteness, redness and wheals.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

INHALED

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of amine vapours may cause irritation of the mucous membrane of the nose and throat, and lung irritation with respiratory distress and cough. Swelling and inflammation of the respiratory tract is seen in serious cases; with headache, nausea, faintness and anxiety. There may also be wheezing.

CHRONIC HEALTH EFFECTS

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Sensitisation may give severe responses to very low levels of exposure, i.e. hypersensitivity. Sensitised persons should not be allowed to work in situations where exposure may occur.

Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing "amine asthma". The literature records several instances of systemic intoxications following the use of amines in epoxy resin systems.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

TOXICITY**IRRITATION****POLYAMIDE RESIN:**

Oral (rat) LD50: 23100 mg/kg
[Man HENK]

Skin (rabbit): Mild [Man H

TRIETHYLENETETRAMINE:

Oral (rat) LD50: 2500 mg/kg
Dermal (rabbit) LD50: 805 mg/kg
Eye (rabbit): 49 mg SEVERE
Eye (rabbit): 20 mg/24h Moderate

Skin (rabbit): 490 mg Open SEVERE
Skin (rabbit): 5 mg/24 SEVERE

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

If container can not be cleaned sufficiently well to ensure none of the original product remains or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION**HAZCHEM**

None

ARDEX WPM 501 - PART A

Chemwatch Material Safety Data Sheet
Issue Date: 11-Mar-2006

Revision No: 2

Hazard Alert Code:
HIGH
Chemwatch 4560-93
CD 2006/2

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN,IATA,IMDG

Section 15 - REGULATORY INFORMATION**POISONS SCHEDULE**

None

REGULATIONS

polyamide resin (CAS No:Not avail):

No regulations applicable

triethylenetetramine (CAS: 112-24-3) is found on the following regulatory lists;

Australia Inventory of Chemical Substances (AICS)

Australia Poisons Schedule

OECD Representative List of High Production Volume (HPV) Chemicals

No data available for polyamide resin as CAS: Not avail.

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 11-Mar-2006
Print Date: 7-Jun-2006